
1. What's corrugated steel sheets?



Corrugated metal roof is using color coated steel or aluminum alloy metal sheets and cold-rolled into various profiled sheets by rolling equipment. Corrugated metal roof or steel sheets are an energy-efficient, low cost, and long-lasting roofing and wall cladding option for homes, log cabins, and commercial building envelope applications.

2. Application:



- 1) Commercial buildings: Wall & Roof;
- 2) Industrial buildings: Wall & Roof;
- 3) Residential buildings: Wall & Roof.

3. Steel roofing material details:


Available length :	20FT container: ≤ 5.95m
Available lelight:	40FT container: ≤ 11.95m
Available material :	PPGI/ PPGL/GI/Color Aluminum sheets/ Al-Mg-Mn alloy metal sheets
PPGI/ PPGL/GI thickness:	0.30~0.80mm
Color Aluminum sheets/ Al-Mg-Mn alloy metal sheets thickness:	0.60~1.20mm
Coating type :	PE, PVDF, HDP, SMP, etc.

4. Product tolerance:

Cut to length	±5mm
Cover width	±2mm
Thickness	±0.02mm
End square	±3mm


5. Metal roofing types:








6. Common flashing drawing for reference:





Xiamen Yumi Imp., & Exp., Co., Ltd.

Add:Unit 1304-3, Building 59, Chengyi North Street, Phase III,Xiamen Software Park, Xiamen,China Tel/Fax:+86-592-6095031 E-mail:manager@yumisteel.com



7. Material certificates reference:











We are cooperating with Bluescope, Bao steel, Shougang group, Guanzhou steel, and Yiehphui steel. All these steel brand are top brand in China, which can make sure you can have good quality sandwich panels. Normally steel standards are China GB Q235, Q345, Q355. Other special steel standards, please indicated, when making inquiry.

The following are material certificate for your reference:



制造厂: 总部

Xiamen Yumi Imp.,&Exp., Co., Ltd. Add:Unit 1304-3, Building 59, Chengyi North Street, Phase III,Xiamen Software Park, Xiamen,China Tel/Fax:+86-592-6095031 E-mail:manager@yumisteel.com

宝砂钢[®] 宝山钢铁股份有限公司 BAOSHAN IRON &STEEL CO.,LTD. 产品质量证明书 INSPECTION CERTIFICATE



上海安全山区富铝路885号 解稿 201900 No.885 Fujin ROAD, BAOSHAN DISTRICT 201900 SHANGHAL P. R. CHINA TEL (021)28649104

	订货单位 CUSTOMER		北京多	3.10	方質易	有限公	id.													15.618 1000UC		彩色	排版等	100						
	包括单位 PURCHASER		.1:WS	:968	输作用	公司 (4	化北方 名	(同)											- 11				0001	58		SE -		o. 1%	CSA01900	2600002
_						DC51D+A	Z 2/1%	50/50 /	A.										SIT	ST #4				N						
	标 准 PECIFICATION		THR.																	SET S		20	19/05/	26						
			PE														4			NSE N							有号 SNO.		09F0	000834
序	00 0 M (c)	REAT HOCK WORTH LENGTH REAT (bg) **10** #10**		\Box																										
9	COIL/PACK	-	HEAT		MICTH		数	MASS	-		-						Y.S.	T.S.	EL			NESS		TOP		29.55	物布	光秤	19.12	"05 反向
0.				- D - DO		con	SHEETS	5-85		-14	214				x10	×10	-		_	SE	gt		100		-62	-	-	_		PP(B)
ď	17370647103							4945		10	20	12		0			342	379	31				100	54	53	20	CK.	33	108	OK.
3	17370647404							4945		10	20	12	-	0			342	324	31				107	54	53	20	OK.	33	05	OK
4	17370648201							4365		29	22	20	9				345	329	34				111	56	50	20	OK.	33	OK.	OK
4								4365		29	22	20	9	G.		Γ.	345	379	34				III	56	55	20	OK.	33	06	OK
6	17370648205	1	27432208	0.50	1200	COIL		4185	40	29	22	20	9				345	379	34				111	56	55	20	OK	33	OK	OK
		L						Ц			U		И	L															Ц	Ш
-1	# ZE REMARKS		·				27585													7										
	注 释 NOTES				STREN	OTH DD(,m)		* TENSIL INCIL HA				20.88	ELA		INGAT		*04.00	G.L.	GAUGE	LENG			1= 5.65 ERSE II				L2= 50N	nu.		L3= 80M
				may c	ERT INV	THET MAI		FEC													W MOO	MOUNTS.				· U	Vic	Χ'n	mode	:
-	会验者 SURVEYOR TO	,				ESTS OF									1130		1m 56	136/6.1	FOR 1 BELS	01.15	ACC	MUNCH. E				质量多	造人 MANA	GER	¥	: [4]





品质证明书 INSPECTION CERTIFICATE

×	diet "		F4.1												CERT	IFECA	68 · 4 TE 30	11973	H.					- is	199	并在	TE	1	2019	/107/30	0		
		PREPAINTED BOT FOR SOME-2S CONTER STUEL IN CORE.											L		R 179	W 500.	1.2660						DELIVERY BATE 2010/02/26										
70	A A M															PRODE		86 10 W	11.19.4	20.00	4												
															SPS	ciril	S. M. SELON	TOP: 19	N. A	ALLE ALLE	CHIR	(20.0	ACT I	ATRIB BCR. I	CS P	R.H.	. 17	4 7	RIAL I	TOT I	UM 0		
	44.		12.0	500	poo	DIREC	150000			WOO	1010	ночи	ES AN	o one	OS								- 00	FA.	P CB	DEFCAL	CON	BL0213	HOW .	FT%			
÷	BNOLE		nic	150	LEPCTH	28	153	A SERVICE	STENSOLE STATE OF THE PARTY.		12	# 5 A		11	42	12 13	24	DESCRIPTION OF	¢	We 34		P	8	81	Co	14	Gr.	100	¥	Mr	Ti	8 7	00
	30.		NO			pos	No.	Nint	N'est	8.76	HIA HA	BOS						Sec.	X10°			X10°				KI	4			210,		X10°	*
		- 1	Social S	OTTON				INF.	DF.	DF.	180"	128110																					Т
62 63 64 65 66 67	0021403200 0021403200 0021403200 0021403200 0021403200 0021403200		6, 576 6, 576 6, 576 6, 576 6, 576 6, 576	1200 1200 1200 1200	922 944 944 944 945		6366 6175 6175 6175 6175 6175 6185 6185	364 364 374 374 374 374 374 374 374	410 410 410	31. 6 31. 6 30. 6 30. 6 30. 6 30. 6	S S S S S S S S S S S S S S S S S S S			PREPRE	医医医氏氏	CK CK CK CK	保保保保保保	OK OK OK OK OK OK	6.1	11	101111111	17 10 10 10 10		HHHHH									
int.	#1: Penci #0: Gross	Carrier Control	が、	観り、朝	ない。)	Salt Sapar	Spray Test	#	***	i, so																						
cı	IRTIFIED T	o isosi	001:20	15		TES	PARTIES.	CERTIFIE	MATERIAL R	MATERI	IAL B	CSCENSID	383	REIN-	HAS	REEN	MANA	SE SE C	ANG						<	6	2	CAS.	34	T. LEE	S	2	



冠州	3	SHANDONG G		田田かくり	1	INSI	ECI	_	CERI	TIFICA	ILL	_	8	B.徐层明卷 inted Steel C		Pax: (0086)0						
订货单位		元品用	出金額	和中国的	1	- 1	PROD			W	-											
CUSTOMER 教養學性	716	-	21:12	PASSING THE			会門		運動化能中								20190915003					
PURCHASER		山东淮	面調明	版有限公司		CONTI			411	0.			CATE NO.	A								
	100	1 7 1	185	CHIM	Church						0.10			杉田期	2019. 09. 15							
6/2	1	G	B/T 127	54-2006	2006 DAT					2019-0	9-12		TIC ISS	UE DATE								
SPECIFICATION		7 8	3		_	-				10		中性能			SAIF 性能 COAT PROPERTY							
		MATERIAL DESCRI					化年成分(N) ICAL COMPOSITION			MERR	TENSILE 1		ST			CORT PROPE						
4H ⊕ ⊕ COIL NO	DR 90		5.8	MB.	С	Si	Mn	P	5	COATING	25	10.12	916年	自用料度 course	光海 uma	設度可由 CONT	の年級式	ESC.				
	CRACE	SIZE	AEIGH.	27	×10 ⁻⁰	×10 ²	=10 ⁻²	×10 ⁻¹	+10*	614	Y.P.	T.S.	EL.	THICKNESS	U.S. C.	врежні	BADWINE					
		(ma*ma)	de	7,1				18	13	60	339	388	30	24/10	38	3T	311	91				
35411905230014C019A	A	0.75*1200	3.604	硅改洛阳白	40	2	19	15	21	60	342	390	- 30	24/10	38	3T	3H	93				
JS411905230021C020A	A	0.75*1200	4.57	经改造制的	50	2	27	_	23	60	329	385	33	24/10	39	3T	3H	93				
JS411905230062C030A	A	0.75*1200	4.038	硅改塔居白	40	1	24	13	-	60	129	379	33	24/10	38	3T	3H	93				
JS411905230034C025A	Α	0.75*1200	4.244	经改造制度	40	2	17	15	10	60	329	379	33	24/10	38	ST.	3H	93				
JS411905230032C023A	A	0.75*1200	4.112	硅改洛阳白	40	2	17	15	10	-	329	379	33	24/00	39	3T	316	91				
JS411905230031C022A	Α .	0.75*1200	4.114	电改造用台	40	2	17	15	10	60	335	380	31	24/10	38	3T	3H	93				
JS411905230042C027A	_	0.75*1200	3,484	磁改造知由	50	1	22	14	19	60	339	388	30	2450	39	3T	3H	92				
JS411905230013C018A	_	0.75*1200	4.03	植改造部位	40	2	19	18	13	60	339	1	1	1	14	0. 1	1	1				
1	1	1	1	1	1	1	1	/	1	+	1	1	1	5	10	1	1	1				
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	-11	1	1				
1	1	1	1	1	1	11	1	1	1	1	1	1	1	1	11	18 18	1	1				
	1	1	1	1	1	1	IN	(55) +	1	96 98	(708)	1	-	-	1	1777	3					

8. Available colors:



Colors above are regarded as our regular color,welcome you to choose from them,if any color meet your demand.For other color,we have the following requirement:

- 1) It's better to send us the color reference in RAL color swatches, then we could have better color reference;
- 2) For unregular color,we have minimum order quantity,it's at least 3000 meters per color.

9. Packing of metal roofing:

☆ Common packing:



Firstly,PVC film to pack steel roofing sheets,then use mildewproof kraft paper to pack outside.

☆ Premium packing:



Firstly,PVC film to pack steel roofing sheets,then use mildewproof kraft paper to pack outside and finally use steel box packing.



10.Panel Delivery:

All deliveries (unless indicated otherwise) are by sea transport to customer appointed port. If some special requirement, like DDP service, please indicate the address in details, so that we will offer you exact shipping cost details. Off-loading is the responsibility of the client. If customers have any doubt of off-loading problem, please feel free to contact us for details, thank you.

11. Maintance for steel sheets

Original design, environment of the installation, and maintenance of the installation is the three main factors that effects on metal sheets lifetime. Maintenance is the biggest factor, so please read the followign details:

- Every 3 months regular inspection for problems, so we could avoid they become major corrosion reason;
- Place near coastal or industrial influences need every 3month regular washing down;
- Remove leaves and other debris from drains, downpipes, guards, tanks, holes and other overflows;
- Keep no soil, concrete and debris near the wall;
- Do not spray pesticides excessively.



12.Our service & support :

☆ Installation instructions:

We can have installation instructions to be offered for each different projects, as per customers' requirement.

☆ Technical support:

If customers have special requirement for on-site guide,we can also have our people to go to customers' project site to support your installation. Please contact our salesman to discuss with this support.

☆ Unloading instructions:

If you have container unloading questions, please feel free to discuss with our team, we will do our best to put forward one container unloading solution for you.

☆ Full set of technical information:

When you have technical information need to be offered for related projects, please contact our salesman, and clarify what you need, and we will have our engineers to offer related information to you.

Yumi steel will do our best to support your projects with professional attitudes and excellent service spirit.